

PH610 - WATER DISCHARGE HOSE - W.P. 20 BAR



Construction

Inner tube	Black colour, Synthetic rubber resistant to water
Reinforcement	Plies of synthetic textile cords
Cover	Black colour, Synthetic rubber, wrapped type, abrasion water resistant
Application	Light weight rubber collapsible hose design for water, natural liquid fertilizers, waste water, for submerged pump and irrigation system

Item Code	Dash Size	ID		OD		WP		BP		W kg/m
		inch	mm	inch	mm	psi	bar	psi	bar	
PH610-16	-16	1	25.0	1.34	34.0	300	20	900	60	0.53
PH610-20	-20	1.1/4	32.0	1.65	42.0	300	20	900	60	0.84
PH610-24	-24	1.1/2	38.0	1.89	48.0	300	20	900	60	0.98
PH610-32	-32	2	51.0	2.44	62.0	300	20	900	60	1.10
PH610-40	-40	2.1/2	63.0	2.99	76.0	300	20	900	60	1.50
PH610-48	-48	3	76.0	3.50	89.0	300	20	900	60	1.72
PH610-56	-56	3.1/2	89.0	4.06	103.0	300	20	900	60	2.10
PH610-64	-64	4	102.0	4.57	116.0	300	20	900	60	2.40
PH610-80	-80	5	127.0	5.59	142.0	300	20	900	60	3.00
PH610-96	-96	6	152.0	6.57	167.0	300	20	900	60	5.00
PH610-128	-128	8	203.0	8.62	219.0	300	20	900	60	7.20



Temperature Range : Continuous: -25°C to +70°C